

# Do you need the right concrete vibration solution right now? VIBCO's rapid customer response team can help.



We're the <sup>CONCRETE</sup> Vibrator Guys.™

## Product Application Bulletin #452 Model US-1600 High Frequency Electric Vibrator

### VIBCO'S SOLUTION

VIBCO recommended the installation of US-1600 High Frequency Electric Vibrators on the column forms. The recommended vibrators were in stock and were delivered next day so that the contractor did not lose valuable time. The vibrators produced superior, blemish-free concrete making it unnecessary for any additional on-site touch ups.

### VIBCO'S BENEFITS

After installing the VIBCO US-1600 High Frequency Electric Vibrators, the customer received the following benefits:

- Kept job on schedule and on budget
- A strong, blemish-free finished product
- Saved man-hours previously lost to on-site touch ups.



US-1600



### COLUMN FORM



## "We were on a really tight schedule..."

The repairs to the bridge columns needed to get done, but we realized that the internal concrete vibrators we had intended to use would not fit the forms - the rebar was in the way. We needed to find an external vibrator that could properly consolidate the concrete and give a superior finish to limit the number of touch-ups. Thank goodness one of our guys had talked to a VIBCO rep at a trade show! VIBCO had the vibrator we needed in stock and they sent it overnight so we were able to keep working on schedule and on budget."

Lead Engineer  
Carson J., New Jersey

### Model US-1600 High Frequency Electric Vibrator

#### CLICK HERE FOR ADDITIONAL TECHNICAL INFORMATION

- 9000 VPM Max Speed Single Phase
- 1600 lbs of force
- 85 dB on A-Scale at 1 meter
- 115 AC-DC Volts
- Intermittent Cycle

### ALTERNATE MODELS

- SVRFS-4000 High Frequency Pneumatic Vibrator
- SVRWS-4000W High Frequency Pneumatic Vibrator

**Call 800-633-0032 for a FREE 10-Day Product Trial**

visit: [www.vibco.com](http://www.vibco.com)

fax: 401-539-2584

e-mail: [vibrators@vibco.com](mailto:vibrators@vibco.com)